

REINFORCED REPAIRABLE HALF PALLET

HEAVY DUTY EXPERT 0806-O3



Half reinforced pallet ideal for transporting fast moving products with maximum efficiency. The runners are repairable, allowing their replacement in case of breakage without having to discard the equipment. Ideal for high reuse.

Advantages

- ✓ Apto Rack
- ✓ Perímetro anti-impacto
- ✓ Esquinas preparadas para un óptimo retráctilado
- ✓ Patines reforzados para caminos de rodillos

Technical data

Ref	Materials	Weigh	Measures	Static load*1	Dynamic load*1	Rack load*1
EXPERT 0806-O3	rPE rPP	8.80 kg [19.40 lb]	800x600x160mm [31.50x23.60x6.30"]	2000 kg [4410 lb]	1000 kg [2210 lb]	500 kg [1105 lb]

Logistic data

Ref	20' DV	40' DV	40 HC	45' PWHC	Tauliner	Mega	Jumbo
EXPERT 0806-O3	325	715	880	1056	1056	1188	1368

REINFORCED REPAIRABLE HALF PALLET


HEAVY DUTY EXPERT 0806-03



Options

- ✓ Color personalizable
- ✓ Etiqueta RFID
- ✓ Logo serigrafiado
- ✓ Logo grabado
- ✓ Topes personalizables o sin topes
- ✓ Otros materiales disponibles

Technical drawing



Iconography legend

- 20°/40°C [-4°/104°F]
- 0°/40°C [32°/104°F]
- open
- 4-ways
- Rims for boxes
- Repairable
- Reinforced

Recommendations for use

- ✓ Do not stack more than 48 pallets, which is equivalent to a height of 7.7 m when empty
- ✓ Do not handle blocks of more than 27 empty pallets.
- ✓ Once stacked in height check that they are properly fitted.

*1 The values indicated are approximate and are based on both practical experiences and ISO 8611 tests with a uniformly distributed standard load, distributed all over the pallet surface, duly consolidated, compact and stable and at ambient temperature (20°C [68°F]) for a specific time. Different load conditions produce different values that have to be checked at the customer's request. Any deterioration or breakage in the pallet may vary these results.

*2 Due to the characteristics of the materials recycled, the dimensions and the weight of the pallets may present certain tolerances. Dimensional tolerances according to DIN ISO 2768-V and weight tolerances: +/- 4%. Except for references of the FLAT category: +/- 3%.

- Nortpalet reserves the right to modify any information herein indicated without prior notice.

- The specifications can be affected in case of alteration of the product with parts and / or materials different from those approved by the Nortpalet quality department. Any warranty, specification or liability on the part of Nortpalet will be terminated in case of modification of the product with spare parts not supplied by Nortpalet.